

Morel 57 series tweeters have a performance which rivals that of our larger tweeters. The sensitivity and most other specs are similar to the MDT-101S tweeter. The difference is that the 57 series are much smaller, extremely versatile and easy to install in any vehicle. These three models are built with a 28mm soft dome, and all have hexatech voice coil technology.

The 57.06 model is a double magnet tweeter and the most efficient of these models (sensitivity of 92 db). All domes are replaceable and the tweeters are packed with grills and brackets.


MDT 57·04

Specification


Voice Coil \varnothing 28mm (1 1/4") x 2.5mm
 Power Handling at 5kHz/12dB **80 Watt**
 Nominal Impedance @ 1kHz 6.4 ohm
 Sensitivity **90dB (1W/1M)**
 Frequency Response **2000—20000 Hz**
 Resonant Frequency **900 Hz**
 DC Resistance **5.2 ohm**

FITTING & MOUNTING OPTIONS

Flush Mounting



Flat Surface Mounting



MDT 57·05

Specification

Voice Coil \varnothing 28mm (1 1/4") x 2.7mm
 Voice Coil Type **Hexatech Aluminium**
 Power Handling at 5kHz/12dB **200 Watt**
 Nominal Impedance @ 1kHz 6.4 ohm
 Sensitivity **91dB (1W/1M)**
 Frequency Response **1800—25000 Hz**
 Resonant Frequency **700 Hz**
 DC Resistance **5.2 ohm**


Angled Mounting Vertical Surfaces



Angled Mounting Horizontal Surfaces Option A



Angled Mounting Horizontal Surfaces Option B



MDT 57·06

Specification

Voice Coil \varnothing 28mm (1 1/4") x 2.7mm
 Voice Coil Type **Hexatech Aluminium**
 Power Handling at 5kHz/12dB **200 Watt**
 Nominal Impedance @ 1kHz 6.4 ohm
 Sensitivity **92dB (1W/1M)**
 Frequency Response **1800—25000 Hz**
 Resonant Frequency **700 Hz**
 DC Resistance **5.2 ohm**

Substituting and Mounting Tweeter in the original car loudspeaker location

